

WORK-PRACTICE DATA SHEET - THIS IS A SUMMARY ONLY - FULL REPORT AVAILABLE

ChemWatch 6540-10 - HAZARDOUS (OSHA) / DANGEROUS (EC) SUBSTANCE, - Company Contact No. (+61 2) 9624 0500

ERS PREMIER GUN WASH

| INGREDIENTS | CAS No | % | TWA |
|---------------------|----------|-------|---------|
| cyclohexanone | 108-94-1 | 1-9 | 50 ppm |
| toluene | 108-88-3 | 30-60 | 150 ppm |
| methyl ethyl ketone | 78-93-3 | 1-9 | 30-60 |
| other ingredients | | | |

UN No: 1993
Hazchem Code: 3[Y]
DG Class: 3
Subsidiary Risk: None

PRECAUTIONS FOR USE

- Glasses:**
Chemical goggles.
- Gloves:**
1. PE/EVAL/PE 2. NITRILE
- Respirator:**
Type A Filter of sufficient capacity
- Flammability:**
Highly flammable.

PROPERTIES

Liquid,
Does not mix with water.
Floats on water.

HEALTH HAZARD INFORMATION

Acute Health Effects:
HARMFUL - May cause lung damage if swallowed.
 Harmful by inhalation and if swallowed.
 Irritating to eyes and skin.
 Can be absorbed through skin.
 Vapours may cause dizziness or suffocation.
 Skin contact may produce health damage*.
 May produce discomfort of the respiratory system*.
 Vapours potentially cause drowsiness and dizziness*.
 * (limited evidence).

Chronic Health Effects:
 Possible risk of harm to the unborn child.
 Harmful: danger of serious damage to health by prolonged exposure through inhalation.
 Exposure may produce irreversible effects*.
 Cumulative effects may result following exposure*.
 * (limited evidence).

SAFE HANDLING INFORMATION

- Storage & Transport:**
 Keep container tightly closed.
 Keep container in a well ventilated place.
 Keep away from sources of ignition. No smoking.
 Store in cool, dry, protected area.
 Restrictions on Storage apply. Refer to Full Report.
- Spills & Disposal:**
 Eliminate ignition sources.
 Prevent from entering drains.
 Contain spillage by any means.
 Control vapour with water spray/fog.
 Absorb with dry agent.
 Stop leak if safe to do so.
 Take off immediately all contaminated clothing.
- Fire/Explosion Hazard:**
 Highly flammable.
 Vapours/ gas heavier than air.
 Toxic smoke/fumes in a fire.
- Fire Fighting:**
 Foam.

FIRST AID

- Swallowed:**
Give water (if conscious). Seek medical advice.
- Eye:**
Wash with running water (15 mins). Medical attention.
- Skin:**
Remove contaminated clothing. Wash with water and soap.
- Inhaled:**
Fresh air. Rest, keep warm. If breathing shallow, give oxygen. Medical attention.

ADVICE TO DOCTOR


Treat symptomatically.
Evaluate for respiratory distress. Consider lavage with cuffed tube. NO adrenalin.



**EPG for ERS PREMIER GUN WASH
CHEMWATCH 6540-10**

CD 2004/4 Page 1 of 3

Product Name: ERS Premier Gun Wash
 Other Names: Manufacturer's Code: 5820, 13219,
 13220, 13276
 ! 03/00
 Shipping Names: FLAMMABLE LIQUID, N.O.S.
 EPG Number: 3A1
 U.N. Number: 1993
 Dangerous Goods Class: 3
 Subsidiary Risk: None
 Hazchem Code: 3[Y]
 Poisons Schedule Number: S5
 Packing group: III



FLAMMABLE LIQUIDS
 FLAMMABLE LIQUID

EMERGENCY CONTACTS

Manufacturer Contact Information
 Company: ERS Australia P/L (Safety Kleen)
 Telephone: (+61 2) 9624 0500
 AUSTRALIAN POISONS INFORMATION CENTRE
 24 HOUR SERVICE :- 13 11 26
 POLICE, FIRE BRIGADE OR AMBULANCE: 000

NEW ZEALAND POISONS INFORMATION CENTRE
 24 HOUR SERVICE: 0800 764 766
 NZ EMERGENCY SERVICES: 111

HAZARD**FIRE**

Liquid and vapour highly flammable.
 Fire may produce irritating or poisonous gases.
 Heat may cause violent rupture of containers.

HEALTH

Vapour may cause dizziness or suffocation especially in confined spaces.
 May irritate or burn eyes or skin.

OTHER

Vapour can travel considerable distance to a source of ignition.
 Vapour may form explosive mixtures with air.

EMERGENCY PROCEDURE**FOR ALL EMERGENCIES**

Shut off engine and electrical equipment.
 No smoking or naked lights within 50 metres.

continued...

**EPG for ERS PREMIER GUM WASH
CHEMWATCH 6540-10**

CD 2004/4 Page 2 of 3

Move people from immediate area; keep upwind.
Warn other traffic.
Send messenger to notify fire brigade and police.
Tell them location, material, quantity, UN Number and emergency contact.
Indicate condition of vehicle and damage observed.

TANKER/VEHICLE ACCIDENT

Carry out action under FOR ALL EMERGENCIES.
Check for spills or leaks.
DO NOT move vehicle if movement could cause spillage or generate sparks.
Warn other traffic.

SPILLS OR LEAKS

Carry out action under FOR ALL EMERGENCIES.
Move people upwind from small spills.
For large spills, or tank rupture, consider initial evacuation distance of 200 metres in all directions.
Avoid breathing vapours and contact with skin and eyes.
Stop leak if safe to do so.
If available, use water spray to disperse vapour.
Small spill: absorb in sand or other non-combustible material.
Place in clean drum then flush area with water.
Prevent spilled material from entering drains by banking with sand or earth.

FIRE

Carry out action under FOR ALL EMERGENCIES.
Consider initial evacuation distance of 100 metres in all directions if tanker or tanker-load is involved in fire.
Stay away from end of fire-exposed tanks and drums.
For minor fires use extinguisher provided (trained personnel).
Fight fire from safe location.
For HAZCHEM 3 use foam, for HAZCHEM 2 use fog or water spray.
If available play water on containers to keep cool.
If fire gets out of control withdraw all personnel from area and warn against entry.

FIRST AID

INHALED

Remove to fresh air, lay down, rest.
If not breathing, apply resuscitation.
Keep warm.
Transport to hospital or doctor.

EYE

Immediately hold eyes open and wash continuously with water for at least 15 minutes.
Transport to hospital or doctor.

SKIN

continued...

**EPG for ERS PREMIER GUM WASH
CHEMWATCH 6540-10**

CD 2004/4 Page 3 of 3

Immediately remove all contaminated clothing, including footwear, after wetting with water if available.
Wash affected areas thoroughly with water, and soap, if available.

BURNS

Immerse affected area in cold water for 10 to 15 minutes.
Bandage lightly with sterile dressing.
Treat for shock if required.
Transport to hospital or doctor.

Issue Date: Tue 18-May-2004
Print Date: Wed 1-Jun-2005